

# DC Code®

## DC3R1


Thermal Receipt Printer

- Support IAP update online
- Support QRcode, PDF417
- Transparent cover design
- Sounds and light alarm function optional.



# DC3R1

## Thermal Receipt Printer



<b>Model</b>		<b>DC3R1</b>
<b>Printing method</b>	Direct thermal	
<b>Paper width</b>	79.5±0.5mm	
<b>Print width</b>	72mm	
<b>Column capacity</b>	576 dots/line or 512 dots/line	
<b>Printing speed</b>	200 mm/s	
<b>Interface</b>	USB	
<b>Line spacing</b>	3.75mm(Adjustable by commands)	
<b>Column number</b>	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns	
<b>Character size</b>	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)	
<b>Cutter</b>		
<b>Auto cutter</b>	Partial	
<b>Barcode Character</b>		
<b>Extension character sheet</b>	PC437(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)	
<b>1D Barcode</b>	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
<b>2D Barcode</b>	QR CODE / PDF417	
<b>Input buffer</b>	96 Kbytes	
<b>NVFlash</b>	256 Kbytes	
<b>Power</b>		
<b>Power adaptor</b>	AC 100~240V, 50 ~ 60Hz	
<b>Printer Input</b>	DC 24V/2.5A	
<b>Cash drawer</b>	DC 24V/1A	
<b>Physical characteristics</b>		
<b>Weight</b>	1.01 Kg	
<b>Dimensions</b>	192*145.2*146.3mm(D*W*H)	
<b>Environmental Requirements</b>		
<b>Work environment</b>	Temperature (0 ~ 45°C) humidity(10 ~ 80%)	
<b>Storage environment</b>	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)	
<b>Reliability</b>		
<b>Cutter life</b>	1.5 million cuts	
<b>Printer head life</b>	150Km	
<b>Software</b>		
<b>Emulation</b>	ESC/POS	
<b>Driver</b>	Windows/JPOS/Linux/OPOS/Android/Mac	
<b>Utility</b>	Windows & Linux test Utility	
<b>SDK</b>	iOS, Android, Windows	

