

UHF FAST series Reader



Support Interface TCP/IP-GSM-WIFI



Support Password/Mask code function can add reading security



Support TID+EPC+USER multi region data mixed reading



Support remote online upgrade and special function customization



Model No - **SRK6GWL**



TCP/IP: Stable network communication, wireless length limitation



WIFI: Network cable power supply, No wiring required, plug & play



GSM: Wireless communication, no wiring required



Reading range 0 to 15mm

Application



Vehicle Management



Warehouse Management



Production Management





Asset Management



Weighscale Management



Technical Parameters:

Model	CF6C1G	CF6C1E
Image	SRK6GWL 	SRK12GWL 
Frequency	865~868MHz(EU) 902~928MHz(US)	865~868MHz(EU) 902~928MHz(US)
Protocol	ISO18000-6C(EPC C1G2)	ISO18000-6C(EPC C1G2)
Chip	High performance chip	Impinj E710
Built-in antenna	12dbi antenna	12dbi antenna
RF output	9dbi antenna 0~33dbm (adjustable)	9dbi antenna 0~33dbm (adjustable)
Reading distance	0~20m	0~25m
Standard interface	0-9 m RS232, WG26, Relay	0-15m RS232, WG26, Relay
Internet interface	TCP/IP, POE, WIFI	TCP/IP, POE, WIFI
Customizable interface	TCP/IP, GSM, WIFI USB, RS485, TTL	TCP/IP, GSM, WIFI USB, RS485, TTL
Working mode	Active/Answer/ Trigger mode	Active/Answer/ Trigger mode
Data filter	support	support
Label RSSI	support	support
Power	9~24V (Provide power adapter)	9~24V (Provide power adapter)
Waterproof level	IP65	IP65
Size	415*415*67mm	415*415*67mm
Weight	3.5kg 2kg	3.5kg 2kg